# (19) World Intellectual Property Organization

International Bureau



### LINEDA BURRINI IN BURRI HARD BERKI BERKI BIRKI BIR KIR KURKI BERKI BERKI BURRI BURRI BURRI BURRI BURRI BERKI BERKI

(43) International Publication Date 18 November 2004 (18.11.2004)

**PCT** 

## (10) International Publication Number WO 2004/100553 A1

(51) International Patent Classification7:

H04N 7/26

(21) International Application Number:

PCT/IB2004/001373

(22) International Filing Date: 28 April 2004 (28.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03300011.8

6 May 2003 (06.05.2003) I

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): DUFOUR, Cécile [FR/FR]; c/o Société Civile SPID, 156, Boulevard Haussmann, F-75008 PARIS (FR). MARQUANT, Gwenaëlle [FR/FR]; c/o Société Civile SPID, 156, Boulevard Haussmann, F-75008 PARIS (FR). VALENTE, Stéphane [FR/FR]; c/o Société Civile SPID, 156, Boulevard Haussmann, F-75008 PARIS (FR).
- (74) Agent: LANDOUSY, Christian; Société Civile SPID, 156, Boulevard Haussmann, F-75008 PARIS (FR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Declaration under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VIDEO ENCODING AND DECODING METHODS AND CORRESPONDING ENCODING AND DECODING DE-VICES

(57) Abstract: The invention relates to an encoding method applied to an input video sequence corresponding to successive scenes subdivided into successive video object planes (VOPs) and generating, for coding all the video objects of said scenes, a coded bit-stream the content of which is described in terms of separate channels and constituted of encoded video data in which each data item is described by means of a bitstream syntax allowing to recognize and decode all the elements of said content, said syntax comprising an additional syntactic information provided for describing independently the type of temporal prediction of the various channels. According to the invention, said additional information is a syntactic element placed at the slice level or the macroblock level in the coded bitstream, and its meaning is either specific for each present channel or shared by all existing channels.



